

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (currently amended) A method for executing application programs, comprising:

receiving at least one application program in a handheld mobile wireless client device, said at least one application program comprising compiled program scripts and non-compiled screen definitions;

activating said at least one application program in said handheld mobile wireless client device;

instantiating [[a]] said run-time engine in said handheld mobile wireless client device; and

executing said at least one application program by said run-time engine in said handheld mobile wireless client device to create screen definitions from said non-compiled screen definitions with said at least one application program at run-time as if said screen definitions had been defined at compile time.

2. (previously presented) The method according to claim 1, further comprising:

registering said at least one application program with an operating system of said handheld mobile wireless client device; and

displaying an icon configured to represent said at least one application program in response to said registration.

3. (previously presented) A method for executing application programs, comprising:

- receiving at least one application program in a client device;
- activating said at least one application program;
- instantiating a run-time engine;
- executing said at least one application program by said run-time engine;
- registering a process identification corresponding to said activated said at least one application program; and
- executing a GO method by said run-time engine.

4. (previously presented) A method for executing application programs, comprising:

- receiving at least one application program in a client device;
- activating said at least one application program;
- instantiating a run-time engine;
- executing said at least one application program by said run-time engine;
- registering a process identification corresponding to said activated said at least one application program;
- executing a GO method by said run-time engine, said GO method comprising:
  - initializing at least one of the following of a jump table, a database table, a screen, and a variable;
  - setting a current screen identification to a first screen; and
  - testing said current screen identification.

5. (original) The method according to claim 4, further comprising:  
ending said GO method in response to said current screen  
identification being set to zero.

6. (original) The method according to claim 4, further comprising:  
retrieving a pointer to a current screen corresponding to said  
current screen identification;  
executing a before-draw code block for said current screen; and  
determining a change in said current screen.

7. (original) The method according to claim 6, further comprising:  
determining whether said current screen identification being set to  
zero in response to said determination of said change in said current screen; and  
terminating said GO method in response to said current screen  
identification being set to zero.

8. (original) The method according to claim 6, further comprising:  
drawing said screen in response to said determination of said  
change being a no-change;  
receiving a menu selection; and  
executing a corresponding code block for said menu selection.

9. (original) The method according to claim 6, wherein said  
execution of said corresponding code block comprises:  
determining a code block number of said corresponding code block;  
and  
returning a false value in response to said determination of said  
code block number being zero.

10. (original) The method according to claim 9, further comprising:  
searching a plurality of code blocks in response to said determination of said code block being non-zero;  
retrieving said corresponding code block in response to said code block number; and  
extracting associated opcodes from said corresponding code block.

11. (original) The method according to claim 10, further comprising:  
extracting an opcode from said associated opcodes; and  
executing a corresponding function of said opcode from a jump table.

12. (original) The method according to claim 11, further comprising:  
terminating said corresponding code block in response to said corresponding function returning a true value.

13. (currently amended) A system for executing application programs, comprising:

a handheld mobile wireless client device comprising a memory and a processor; and

a run-time engine residing in said memory and executing on said processor to create screen definitions from non-compiled screen definitions with an application program at run-time as if said screen definitions had been defined at compile time;

wherein said handheld mobile wireless client device is configured to receive at least one application program, said at least one application program comprising compiled program scripts and said non-compiled said screen definitions, said at least one application program configured to instantiate said run-time engine in response to an activation of said at least one application program and configured to execute said at least one application program by said run-time engine.

14. (previously presented) The system according to claim 13, wherein:

said handheld mobile wireless client device is further configured to register said at least one application program with an operating system of said handheld mobile wireless client device and to display an icon configured to represent said at least one application program in response to said registration.

15. (currently amended) A system for executing application programs, comprising:

a client device comprising a memory and a processor;

a run-time engine residing in said memory and executing on said processor;

wherein said client device is configured to receive at least one application program, said at least one application program comprising compiled program scripts and non-compiled screen definitions, said at least one application program configured to instantiating said run-time engine in response to an activation of said at least one application program and configured to execute said at least one application program by said run-time engine; and

wherein said client device is further configured to register a process identification corresponding to said activated said at least one application program and said run-time engine is configured to execute a GO method, said GO method being configured to create said screen definitions from said non-compiled screen definitions with said run-time engine at run-time as if said screen definitions had been defined at compile time.

16. (previously presented) A system for executing application programs, comprising:

a client device comprising a memory and a processor;

a run-time engine residing in said memory and executing on said processor;

wherein said client device is configured to receive at least one application program, configured to instantiating said run-time engine in response to an activation of said at least one application program and configured to execute said at least one application program by said run-time engine;

wherein said client device is further configured to register a process identification corresponding to said activated said at least one application program and said run-time engine is configured to execute a GO method; and

wherein said GO method comprises:

initializing at least one of the following of a jump table, a database table, a screen, and a variable;

setting a current screen identification to a first screen; and

testing said current screen identification.

17. (original) The system according to claim 16, wherein said GO method further comprises:

ending said GO method in response to said current screen identification being set to zero.

18. (original) The system according to claim 16, wherein said GO method further comprises:

retrieving a pointer to a current screen corresponding to said current screen identification;

executing a before-draw code block for said current screen; and

determining a change in said current screen.

19. (original) The system according to claim 18, wherein said GO method further comprises:

determining whether said current screen identification being set to zero in response to said determination of said change in said current screen; and  
terminating said GO method in response to said current screen identification being set to zero.

20. (original) The system according to claim 18, wherein said GO method further comprises:

drawing said screen in response to said determination of said change being a no-change;  
receiving a menu selection; and  
executing a corresponding code block for said menu selection.

21. (original) The system according to claim 18, wherein said execution of said corresponding code block comprises:

determining a code block number of said corresponding code block;  
and  
returning a false value in response to said determination of said code block number being zero.

22. (original) The system according to claim 21, wherein said execution of said corresponding code block comprises:

searching a plurality of code blocks in response to said determination of said code block being non-zero;  
retrieving said corresponding code block in response to said code block number; and  
extracting associated opcodes from said corresponding code block.

23. (original) The system according to claim 22, wherein said execution of said corresponding code block comprises:

extracting an opcode from said associated opcodes; and  
executing a corresponding function of said opcode from a jump table.

24. (previously presented) The system according to claim 23, wherein said execution of said corresponding code block comprises:

terminating said corresponding code block in response to said corresponding function returning a true value.

25. (currently amended) A computer readable storage medium on which is embedded one or more computer programs, said one or more computer programs implementing a method of executing application programs, said one or more computer programs comprising a set of instructions for:

receiving at least one application program in a handheld mobile wireless client device, said at least one application program comprising compiled program scripts and non-compiled screen definitions;

activating said at least one application program in said handheld mobile wireless client device;

instantiating ~~[[a]]~~ said run-time engine in said handheld mobile wireless client device; and

executing said at least one application program by said run-time engine in said handheld mobile wireless client device to create said screen definitions from said non-compiled screen definitions with said run-time engine at ~~least one application program~~ at run-time as if said screen definitions had been defined at compile time.



26. (previously presented) The computer readable storage medium in according to claim 25, said one or more computer programs further comprising a set of instructions for:

registering said at least one application program with an operating system of said handheld mobile wireless client device; and

displaying an icon configured to represent said at least one application program in response to said registration.

27. (currently amended) A computer readable storage medium on which is embedded one or more computer programs, said one or more computer programs implementing a method of executing application programs, said one or more computer programs comprising a set of instructions for:

receiving at least one application program, said at least one application program comprising compiled program scripts and non-compiled screen definitions;

activating said at least one application program;

instantiating ~~[[a]]~~ said run-time engine;

~~executing said at least one application program by said run-time engine;~~

registering a process identification corresponding to said activated said at least one application program; and

executing a GO method by said run-time engine, said GO method being configured to create said screen definitions from said non-compiled screen definitions with said run-time engine at run-time as if said screen definitions had been defined at compile time.

28. (previously presented) A computer readable storage medium on which is embedded one or more computer programs, said one or more computer programs implementing a method of executing application programs, said one or more computer programs comprising a set of instructions for:

- receiving at least one application program;
- activating said at least one application program;
- instantiating a run-time engine;
- executing said at least one application program by said run-time engine;
- registering a process identification corresponding to said activated said at least one application program;
- executing a GO method by said run-time engine;
- initializing at least one of the following of a jump table, a database table, a screen, and a variable;
- setting a current screen identification to a first screen; and
- testing said current screen identification.

29. (original) The computer readable storage medium in according to claim 28, said one or more computer programs further comprising a set of instructions for:

- ending said GO method in response to said current screen identification being set to zero.

30. (original) The computer readable storage medium in according to claim 28, said one or more computer programs further comprising a set of instructions for:

- retrieving a pointer to a current screen corresponding to said current screen identification;
- executing a before-draw code block for said current screen; and
- determining a change in said current screen.

31. (original) The computer readable storage medium in according to claim 30, said one or more computer programs further comprising a set of instructions for:

determining whether said current screen identification being set to zero in response to said determination of said change in said current screen; and  
terminating said GO method in response to said current screen identification being set to zero.

32. (original) The computer readable storage medium in according to claim 30, said one or more computer programs further comprising a set of instructions for:

drawing said screen in response to said determination of said change being a no-change;  
receiving a menu selection; and executing a corresponding code block for said menu selection.

33. (original) The computer readable storage medium in according to claim 30, said one or more computer programs further comprising a set of instructions for said execution of said corresponding code block comprises:

determining a code block number of said corresponding code block;  
and  
returning a false value in response to said determination of said code block number being zero.

34. (original) The computer readable storage medium in according to claim 33, said one or more computer programs further comprising a set of instructions for said execution of said corresponding code block comprises:

searching a plurality of code blocks in response to said determination of said code block being non-zero;

retrieving said corresponding code block in response to said code block number; and

extracting associated opcodes from said corresponding code block.

35. (original) The computer readable storage medium in according to claim 34, said one or more computer programs further comprising a set of instructions for said execution of said corresponding code block comprises:

extracting an opcode from said associated opcodes; and

executing a corresponding function of said opcode from a jump table.

36. (original) The computer readable storage medium in according to claim 35, said one or more computer programs further comprising a set of instructions for said execution of said corresponding code block comprises:

terminating said corresponding code block in response to said corresponding function returning a true value.